

MONOLATERAL EDGEBANDER SMART S600-23 plus e S650-23 plus


Modello – Model - Modéle – Modell - Modelo	S600-23 PLUS	S650-23 PLUS
Spessore pannello - Panel thickness Espaisseur panneau – Werkstückdicke Espesor panel	10 ÷ 80 mm	10 ÷ 80 mm
Larghezza pannello – Panel width Largeur panneau – Werkstücklänge Largo panel	min. 60 mm	min. 60 mm
Larghezza bordo – Edge width Largeur chant – Kantenbreite Anchura canto	15 ÷ 85 mm	15 ÷ 85 mm
Spessore bordo – Edge thickness Espaisseur chant – Kantendicke Espesor canto	0,4 ÷ 12 mm (STD)	0,4 ÷ 12 mm (STD)
Avanzamento – Feed – Advancement – Vorschub - Avance	10-20 mt/min (STD)	10-20 mt/min (STD)
Voltaggio – Voltage – Voltage – Spannung - Voltaje	220/380 V 50/60 Hz – 3Ph +N	220/380 V 50/60 Hz – 3Ph +N
Lunghezza pannello – Panel length – Longueur panel – Werkstücklänge Largo panel	min. 140 (PVC)	min. 140 (PVC)
Potenza installata – Installed power – Puissance installée – Leistung installierte – Potencia instalada	14,2 kw	15,6 kw
Potenza pneumatica – Pneumatic power – Puissance pneumatique – Leistung pneumatic – Potencia neumatico	6 bar	6bar
Peso kg – Weight Kgs. – Poids Kgs. – Gewicht Kgs. – Peso Kgs.	1700	1800

