



Modello – Model - Modéle – Modell - Modelo	M200-23	M400-23
Spessore pannello - Panel thickness Espaisseur panneau – Werkstückdicke Espesor panel	10 ÷ 45 mm 60 mm with opt. 15	10 ÷ 45 mm 60 mm with opt. 15
Larghezza pannello – Panel width Largeur panneau – Werkstücklänge Largo panel	min. 60 mm	min. 60 mm
Larghezza bordo – Edge width Largeur chant – Kantenbreite Anchura canto	12 ÷ 48 mm	12 ÷ 48 mm
Spessore bordo – Edge thickness Espaisseur chant – Kantendicke Espesor canto	0,4 ÷ 6,0 mm with syncro unit max 3,0 mm	0,4 ÷ 6,0 mm with syncro unit max 3,0 mm
Avanzamento – Feed – Advancement – Vorschub - Avance	7,0 mt/min (STD)	7,0 mt/min (STD)
Voltaggio – Voltage – Voltage – Spannung - Voltaje	220/380 V 50/60 Hz – 3Ph +N	220/380 V 50/60 Hz – 3Ph +N
Lunghezza pannello – Panel length – Longueur panel – Werkstücklänge Largo panel	min. 120 (PVC)	min. 120 (PVC)
Potenza installata – Installed power – Puissance installée – Leistung installierte – Potencia installada	3,2 kw	3,4 kw
Potenza pneumatica – Pneumatic power – Puissance pneumatique – Leistung pneumatic – Potencia neumatico	6 bar	6bar
Peso kg – Weight Kgs. – Poids Kgs. – Gewicht Kgs. – Peso Kgs.	920	1000