

## Bordatrice monolaterale mod. RAPID rx200 – rx300 – rx400 – rx500



Modello – Model – Modèle – Modell - Modelo	<b>RX 600</b>	<b>RX 700</b>	<b>RX 754</b>	<b>RX 800</b>
Spessore pannello – Panel thickness – Espaisseur panneau – Werkstückdicke – Espesor panel	10 ÷ 60 mm (STD) 10 ÷ 120 mm with opt. n° 15	10 ÷ 60 mm (STD) 10 ÷ 120 mm with opt. n° 15	10 ÷ 60 mm (STD) 10 ÷ 120 mm with opt. n° 15	10 ÷ 60 mm (STD) 10 ÷ 120 mm with opt. n° 15
Larghezza pannello – Panel width – Largeur panneau – Werkstückdicke – Largo panel	min. 60 mm	min. 60 mm	min. 60 mm	min. 60 mm
Spessore bordo – Edge thickness – Espaisseur chant – Kantendicke – Espesor cant	0,4 ÷ 16mm (STD) 0,4 ÷ 20 mm with opt. 30-31	0,4 ÷ 16mm (STD) 0,4 ÷ 20 mm with opt. 30-31	0,4 ÷ 16mm (STD) 0,4 ÷ 20 mm with opt. 30-31	0,4 ÷ 16mm (STD) 0,4 ÷ 20 mm with opt. 30-31
Avanzamento variabile – Feed – Avancement – Vorschub - Avance	10 – 25 m/min	10 – 25 m/min	10 – 25 m/min	10 – 25 m/min
Voltaggio – Voltage – Voltage – Spannung - Voltaje	220/380 V 50/60 Hz – 3 Ph + N	220/380 V 50/60 Hz – 3 Ph + N	220/380 V 50/60 Hz – 3 Ph + N	220/380 V 50/60 Hz – 3 Ph + N
Lunghezza pannello – Panel length – Largeur panel - Werkstücklänge	min. 140 (PVC)	min. 140 (PVC)	min. 140 (PVC)	min. 140 (PVC)
Potenza installata – Installed power – Puissance installée – Leistung installierte – Potencia installada	13,5 kw	23,1 kw	27,8 kw	29 kw
Potenza pneumatica – Pneumatic power – Puissance pneumatique – Leistung pneumatic – Potencia neumatico	6 bar	6 bar	6 bar	6 bar
Peso kg – Weight kgs – Poids kgs – Gewicht kgs – Peso kgs	2100 (STD) 2600 with opt.34	2350 (STD) 2850 with opt. 34	2870 (STD) 3370 with opt. 34	3200 (STD) 3700 with opt. 34